| | | |

| ProLiant series | c-Class workstation blades | c-Class server blades | Core | Integrity blades | Integrity rack server | Superdome |
|---|---|---|---|---|---|---|
| | WS460c Gen8 | BL420c Gen8 | BL460c Gen8 | BL465c Gen8 | DL560 Gen8 | DL580 Gen8 | DL585 G7 | DL980 G7 | rx2800 | BL620c G7 | BL660c Gen8 | BL680c G7 | BL685c G7 | BL860c/870c/890c i4 | Superdome |
| Typical applications | Multi-display hardware-accelerated graphics performance for 2D, 3D, and streaming video applications | BL420c Gen8 redefines the term "entry-level" in the blade market. It spans everything from single applications and small deployments to essential enterprise workloads, making it ideal for midmarket and cost-sensitive enterprise customers. | The BL460c Gen8 is designed for a wide variety of mainstream business to HPC scale-out apps for small, medium and enterprise data centres. Key workloads include virtualisation, IT infrastructure (file and print, networking, security, systems management), Web infrastructure (Web serving, streaming media) and collaborative (email, workgroup). | The first server blade to deliver over 2,000 cores per rack. With enhanced innovations in performance, flexibility in networking options, and robust management features, the BL465c Gen8 is the price/performance choice for virtualisation, database, and high-performance computing workloads. | The DL560 Gen8 is a new server that offers the ideal four-socket (4S) dense form factor without compromising on performance, scalability, and expandability. | Enterprise-grade 4S x86 server offering breakthrough performance, rock-solid reliability, and compelling consolidation and manageability efficiencies. It is ideal for mission-critical enterprise, business intelligence, and database applications. | Versatile workhorse for the evolving data centre 4P multi-core rackmount server. Ideal for server virtualisation, server consolidation, multi-tiered enterprise applications, and corporate infrastructure applications. | Delivers balanced scaling, self-healing resiliency, and breakthrough efficiency to handle the demands of x86 compute environments: data intensive workloads, decision support, in-memory database, OLTP, large-scale consolidation and virtualising many workloads. Mission-critical and industry-standard design principles suit RISC migration initiatives. | This is the smallest server capable of running HP-UX or OpenVMS. Ideal for distributed mission-critical workloads running in branch offices and rackmount server data centres. The i4 version supports up to 16 cores running HP-UX. The i2 version supports Up to eight cores running OpenVMS. In a 2U chassis, the rx2800 delivers high performance and balanced I/O. | The world's most scalable 2P, single-wide, full-height server in a single full-height blade provides virtualisation efficiency for larger consolidation projects and a variety of demanding data-intensive workloads. | Redefining density-optimised 4S blade technology, the BL660c Gen8 is a new server blade that offers the ideal 4-socket dense form factor without compromising on performance, scalability, and expandability. | Ideal for 4P rack to blade transition, large virtualisation, large databases, ERP, HRM and CRM, terminal services, large e-commerce, electronic design automation, and other very data-demanding applications. | Ideal for virtualisation, multi-tiered enterprise applications, such as SAP, PeopleSoft, Siebel, Oracle® and JDE; server consolidation; large database applications including ERP, CRM, mail and messaging; and business integration applications, such as EDA, petrochemical, life sciences, and material sciences. | HP-UX and OpenVMS enterprise applications can take advantage of the HP BladeSystem with scalable Integrity blades that grow in-box from 2-sockets/16-cores to 8-sockets/64-cores as more CPU or I/O capacity is required. Start small and never run out of headroom. When you need more power, connect up to four blades for perfect scale-up. | Integrity Superdome 2 consolidates and modernises UNIX® applications. It is also used for for mainframe replacement. Ideal workloads are: business processing (DB, ERP, CRM, batch); decision support (data warehouse, business intelligence); large-scale consolidation (including virtualisation and multi-tier). Superdome provides the highest levels of UNIX® application availability and scalability using a modern blade infrastructure. |
| Processors<br>*ES-2697 v2, ES-2695 v2, ES-2690 v2, ES-2680 v2, ES-2670 v2, ES-2660 v2, ES-2650 v2, ES-2650L v2, ES-2667 v2, ES-2643 v2, ES-2637 v2, ES-2640 v2, ES-2630 v2, ES-2630L v2, ES-2620 v2, ES-2609 v2, ES-2603 v2<br>**ES-2690, ES-2680, ES-2670, ES-2667, ES-2665, ES-2660, ES-2650, ES-2650L, ES-2643, ES-2640, ES-2637, ES-2630, ES-2630L, ES-2620, ES-2609, ES-2603<br>Additional processor models are available on request. Please check the product QuickSpecs for more details. | Up to two Intel® Xeon® E5-2600 series processors (4/6/8/10/12 core, including low-power models); Models: E5-2600 v2 series* and E5-2600 series** | Up to two Intel® Xeon® E5-2400 series processors (4/6/8/10 core, including low-power models); Models: E5-2470 v2, E5-2450 v2, E5-2440 v2, E5-2430 v2, E5-2420 v2, E5-2407 v2, E5-2403 v2, E5-2450L v2, E5-2430L v2, E5-2470, E5-2450, E5-2450L, E5-2440, E5-2430, E5-2430L, E5-2420, E5-2407, E5-2403 | Up to two Intel® Xeon® E5-2600 series processors (4/6/8/10/12 core, including low-power models); Models: E5-2600 v2 series* and E5-2600 series** | Up to two Intel® Xeon® E5-4600 series processors (4/6/8 core including low-power model); Models: E5-4650, E5-4650L, E5-4640, E5-4620, E5-4617, E5-4610, E5-4607, E5-4603 | One or more Intel® Xeon® (6/8/10/12/15 core) processors depending on model: E7-4890 v2, E7-4880 v2, E7-4870 v2, E7-8880L v2, E7-4860 v2, E7-4850 v2, E7-8857 v2, E7-4830 v2, E7-8891 v2, E7-4820 v2, E7-4809 v2, E7-8893 v2 | Two to four AMD Opteron™ 6200 or 6300 series processors (including low-power models); Models: 6385SE, 6380, 6378, 6376, 6366HE, 6284SE, 6278, 6282SE, 6276, 6274, 6262HE, 6348, 6344, 6238, 6234, 6176SE, 6174, 6172, 6168, 6164HE, 6166HE, 6176, 6180SE, 6328, 6320, 6220, 6212, 6128, 6132HE, 6136, 6140, 6308, 6204 | Up to four or eight Intel® Xeon® series processors; Models: E7-2850, E7-2860, E7-4870, E7-2830, E7-4807 | Up to two Intel® Itanium® 9500 series processors (i4 generation for HP-UX) or up to two 9300 series processors (i2 generation for OpenVMS) | One or two Intel® Xeon® series (6/8/10 core) processors; Models: E7-2870, E7-2860, E7-2850, E7-8867L, E7-2830, E7-2820, E7-2803 | Up to four Intel® Xeon® E5-4600 series (4/6/8 core) processors; Models: E5-4650, E5-4650, E5-4640, E5-4620, E5-4617, E5-4610, E5-4607, E5-4603 | Two, three, or four Intel® Xeon® series (6/8/10 core) processors; Models: E7-4870, E7-4860, E7-4850, E7-8867L, E7-4830, E7-4820, E7-4807 | Up to four AMD Opteron™ series (4/8/12/16 core) processors; Models: 6380, 6378, 6278, 6376, 6276, 6274, 6272, 6366HE, 6262HE, 6348, 6344, 6238, 6234, 6176, 6174, 6164HE, 6164HE, 6328, 6220, 6320, 6212, 6140, 6136, 6132HE, 6128HE, 6124HE, 6308, 6204 | i4 generation for HP-UX; i2 generation for OpenVMS. - i4: one to eight Intel® Itanium® processor 9500 series/8-core processors (4-64 cores) - i2: one to eight Intel® Itanium® processor 9300 series/4-core processors (2-32 cores) | Start small and grow, from two to 32 sockets containing Intel® Itanium® processor 8500 series/8-core processors. Up to 256 cores in a single system image, or virtualised in hard and soft partitions. |
| Form factor | 16 workstations blades or eight workstations paired with eight graphics expansion blades in a 10U c7000 enclosure; eight workstations blades or four workstations paired with four graphics expansion blades in a 6U c3000 enclosure | 16 server blades in 10U (c7000 enclosure) or eight blades in 6U (c3000 enclosure) | 16 server blades in 10U (c7000 enclosure) or eight blades in 6U (c3000 enclosure) | 16 server blades in 10U (c7000 enclosure) or eight blades in 6U (c3000 enclosure) | Rack (2U) | Rack (4U) | Rack (4U) | Rack (8U) | Rack (2U) | Eight blades in 10U (c7000) or four blades in 6U (c3000) | Eight blades in 10U (c7000) or four blades in 6U (c3000) | Four blades in 10U (c7000) or two blades in 6U (c3000) | Eight blades in 10U (c7000) or four blades in 6U (c3000) | Full-length blades for 10U (c7000) or 6U (c3000) enclosure. - BL860c i4 = one blade, eight blades in a c7000 - BL870c i4 = two blades, four blades in a c7000 - BL890c i4 = four blades, two blades in a c7000 | Available in a choice of up to: - Eight sockets in an 18U enclosure - 16 sockets in an 18U enclosure - 32 sockets, spanning two 18U enclosures. - (16) two-socket blades can be connected, scaling CPU, memory, and I/O as needed. Additional multiple 4U I/O extenders offer practically limitless I/O. |
| Memory (standard for pre-configured models/maximum) | 16 DIMM slots - Standard: 32 GB (4 x 8 GB) DDR3 1600 MHz RDIMMs at 1.5 V One of the following depending on model - Maximum (LRDIMM): 512 GB (16 x 32 GB) up to 1333 MHz at 1.35 V - Maximum (RDIMM): 256 GB (16 x 16 GB) up to 1600 MHz at 1.5 V or 384 GB (16 x 24 GB) up to 1333 MHz at 1.35 V - Maximum (UDIMM): 128 GB (16 x 8 GB) up to 1600 MHz at 1.5 V | 12 x DDR3 DIMM memory slots (six per processor) - Standard: 12 GB (3 x 4 GB) DDR3 1333 MHz RDIMMs at 1.35 V or 24 GB (6 x 4 GB) DDR3 1600 MHz RDIMMs at 1.5 V - Maximum (LRDIMM): 384 GB (12 x 32 GB) up to 1600 MHz at 1.5 V or 192 GB (12 x 16 GB) up to 1333 MHz at 1.35 V - Maximum (UDIMM): 96 GB (12 x 8 GB) up to 1600 MHz at 1.5 V or 96 GB (12 x 8 GB) up to 1333 MHz at 1.35 V | - Standard: variety of configurations from 16 GB (2 x 8 GB) 1333 MHz to 64 GB (8 x 8 GB) DDR3 1600 MHz RDIMMs 1.35 V or 1.5 V - Maximum (LRDIMM): 512 GB (16 x 32 GB) up to 1333 MHz at 1.35 V - Maximum (RDIMM): 256 GB (16 x 16 GB) up to 1600 MHz at 1.5 V or 384 GB (16 x 24 GB) up to 1333 MHz at 1.35 V - Maximum (UDIMM): 128 GB (16 x 8 GB) up to 1600 MHz at 1.5 V | - Standard: 16 GB (2 x 8 GB) DDR3 1333 MHz RDIMMs at 1.35 V - Maximum (LRDIMM): 512 GB (16 x 32 GB) at 1333 MHz - Maximum (RDIMM): 256 GB (16 x 16 GB) up to 1600 MHz | - Standard (entry model): 16 GB (1 x 4 GB) PC3L-10600R (DDR3-1333) RDIMMs - Standard (base models): 32 GB (4 x 4 GB) PC3L-10600R (DDR3-1333) RDIMMs - Standard (high-performance models): 64 GB (4 x 8 GB) PC3-12800R (DDR3-1600) RDIMMs - Maximum capacity (RDIMM): 1.5 TB (48 x 32 GB RDIMM @1600 MHz) | - Up to eight memory cartridges are supported for 96 DIMM slots - RDIMMs: HP 4 GB 1R x 4 PC3-14900R-13 Kit or HP 4 GB 1R x 4 PC3L-12800R-11 Kit or HP 8 GB 1R x 4 PC3-14900R-13 Kit or HP 8 GB 1R x 4 PC3L-12800R-11 Kit or HP 16 GB 2R x 4 PC3-14900R-13 Kit or HP 16 GB 2R x 4 PC3L-12800R-11 Kit - LRDIMMs: HP 32 GB 4R x 4 PC3-14900L-13 Kit - Memory expansion options: HP DL580 Gen8 12 DIMM memory cartridge | Performance models: - 128 GB (16 x 8 GB) of PC3-10600R (DDR3-1333) - 64 GB (8 x 8 GB) of PC3-10600R (DDR3-1333) - 64 GB (16 x 4 GB) of PC3-10600R (DDR3-1333) - 32 GB (8 x 4 GB) of PC3-10600R (DDR3-1333) - 32 GB (8 x 4 GB) of PC3L-10600R (DDR3-1333) Base models: - 32 GB (8 x 4 GB) of PC3-10600R (DDR3-1333) - Maximum: 1.5 TB | Up to 4 TB low-voltage RAM: - 2 GB (1 x 2 GB) dual rank x 8 PC3-10600 (DDR3-1333) - 4 GB (1 x 4 GB) single-rank x 4 PC3L-10600 (DDR3-1333) - 8 GB (1 x 8 GB) dual rank x 4 PC3L-10600 (DDR3-1333) - 16 GB (1 x 16 GB) dual rank x 4 PC3L-10600 (DDR3-1333) - 32 GB (1 x 32 GB) quad rank x 4 PC3L-8500R-7 (DDR3-1333) Registered CAS-9 LP Memory Kit | Up to 384 GB system memory with low-voltage (1.35 V) 16 GB DIMMs | - Type: DDR3-1333 and DDR3-1066 RDIMMs (operating up to 1066 MHz) - Standard: 32 GB (4 x 8 GB) - Maximum: 1.0 TB (32 x 32 GB RDIMMs) | - Standard (pre-configured models): 128 GB (8 x 16 GB) DDR3-1600 MHz RDIMMs at 1.5 V or 128 GB (8 x 16 GB) DDR3-1333 MHz RDIMMs at 1.35 V - Maximum (LRDIMM): 1.0 TB (32 x 32 GB) up to 1333 MHz at 1.35 V - Maximum (RDIMM): 512 GB (32 x 16 GB) up to 1600 MHz at 1.5 V or 768 GB (32 x 24 GB) up to 1333 MHz at 1.35 V | - Type: DDR3-1333 and DDR3-1066 RDIMMs (operating up to 1066 MHz) - Standard: 64 GB (8 x 8 GB) - Maximum: 2.0 TB (64 x 32 GB RDIMMs) | - Standard (depending on model): 64 GB (16 x 4 GB) - Maximum (RDIMM): 1 TB (32 x 32 GB) at 1066 MHz or at 800 MHz - Maximum (RDIMM): 1 TB (32 x 32 GB) at 1333 MHz | - BL860c i4: up to 384 GB DDR3 RDIMMs - BL870c i4: up to 768 GB in 48 RDIMMs - BL890c i4: up to 1.5 TB in 96 DIMMs | Up to 8 TB of DDR3 memory with double-chip spare |
| I/O slots | - Mezzanine I/O expansion slots: PCI-e 3.0 x (16) - Dual-port 10 Gb FlexFabric and 1G Gb Flex-10 - Dual-port 8 Gb Fibre Channel - HBA QDR and FDR InfiniBand - Graphics support: NVIDIA Quadro 500m (single or dual), Quadro 1000m (single, up to eight), Quadro 3000m (single, up to six) - With graphics exp. blade: - Multi GPU graphics Carrier NVIDIA Q4000, Q5000, Q6000, and M2070Q - ATI FS9350 | Two mezzanine I/O expansion slots: (1) PCI Gen3 x (16), (1) PCI Gen3 x (8); 1 GbE, 10 Gb Flex-10, 10 Gb FlexFabric, 8 Gb Fibre Channel, QDR and FDR InfiniBand, I/O accelerator | Two mezzanine I/O expansion slots: (2) PCI Gen 3 x (16); 1 GbE, 10 Gb Flex-10, 10 Gb FlexFabric, 8 Gb Fibre Channel, QDR and FDR InfiniBand, I/O accelerator | Two mezzanine I/O expansion slots: (1) PCI Gen2 x (16), (1) PCI Gen2 x (8); 1 GbE, 10 Gb Flex-10, 10 Gb FlexFabric, 8 Gb Fibre Channel, QDR and FDR InfiniBand, I/O accelerator | - Slot 1: (1) PCI-e 3.0 x (16) FL/FH (x 16 connector) - Slot 2: (1) PCI-e 3.0 x (8) HL/FH (x 8 connector) - Slot 3: (1) PCI-e 2.0 x (4) HL/FH (x 8 connector) - Optional: 3-slot riser x (16), x (8), x (8), or 2-slot x (16), x (16) | Up to nine slots supported; all full length/full height - Standard: (4) PCI-e 3.0 x (8) (5) PCI-e 3.0 x (16) | Up to 11 total slots (standard + optional card) and five embedded standard I/O slots: (3) PCI-e Gen2 x (8) FH/FL, (2) PCI-e Gen2 x (16) FH/FL, optional mezzanine cards (all FH/FL), PCI-e I/O 6-slot expansion, (4) PCI-e Gen2 x (8) + (2) PCI-e Gen2 x (16), or combo PCI-e/PCI-X expansion, (1) PCI-e Gen2 x (16) + (2) PCI-e Gen2 x (8) + (1) PCI-e Gen2 x (4) + (2) PCI-X | - Up to 16 slots supported: 11 full length/full height and five low-profile slots - Base I/O backplane configuration: (2) PCI-e 2.0 x (8), (3) PCI-e x (4) - Optional full-height/ full-length I/O backplanes (choose only one): (2) PCI-e 2.0 x (16), (1) PCI-e 2.0 x (4), (2) PCI-X, or (4) PCI-e 2.0 x (8), (1) PCI-e 2.0 x (4), (1) PCI-e 1, (1) x (4) - Optional low-profile I/O backplane: (4) PCI-e 2.0 x (8), (1) PCI-e 2.0 x (4) | Six I/O slots: - Two full-length PCI-e slots over - Two half-length PCI-e slots - Two low-profile PCI-e above P410i RAID controller | Three mezzanine I/O expansion slots for: 1GbE, 10GbE, 10GbE Flex-10, 10 Gb FlexFabric, 4 Gb and 8 Gb Fibre Channel, iSCSI initiator, QDR (40 Gb/s) InfiniBand, I/O accelerator Smart Array, and PCI-e Mezzanine Pass-Thru adapters | Three mezzanine I/O expansion slots for: 1GbE, 10GbE, 10 Gb Flex-10, 10 Gb FlexFabric, 8 Gb Fibre Channel adapters, QDR and FDR InfiniBand, I/O accelerator | Seven mezzanine I/O expansion slots: - One dedicated to a dual-port LAN adapter, including 1GbE, 10GbE, 10GbE Flex-10, and 10 Gb FlexFabric - The remaining six general purpose for 1GbE, 10GbE, 10GbE Flex-10, 10 Gb FlexFabric, 4 Gb and 8 Gb Fibre Channel, iSCSI initiator, QDR (40 Gb/s) InfiniBand, I/O accelerator, and Smart Array adapters | Three mezzanine I/O expansion slots for: 1 Gb, 10 Gb, and Flex-10/ FlexFabric FCoE-capable 10 Gb Ethernet adapters, iSCSI adapters, 4 Gb and 8 Gb Fibre Channel adapters, and 4 x QDR (40 Gb/s) InfiniBand adapters | Per blade: - x 2 for BL870c and x 4 for BL890c - Six I/O expansion slots via mezzanine cards - Eight integrated HP NC553i 10 Gb FlexFabric adapter ports supporting 10 Gb/ 1 Gb autosensing Ethernet, FCoE, Flex-10, and TCP/IP offload engine | **PCI-e 8x Gen2 slots:** - 48 external SD2-8s - 96 external SD2-16s - 96 external SD2-32s The I/O expansion enclosure (IOX) is used across the entire Superdome 2 product family. The IOX consists of a single board with two I/O hubs (IOHs). Each IOH supports up to six 8x PCI-express cards. **Supports up to:** - Four IOXs SD2-8s - Eight IOXs SD2-16s - Eight IOXs SD2-32s |
| Storage controller | 1 x HP Smart Array P220i controller with 512 MB FBWC, RAID 0 and 1 support, and upgradeable firmware with recovery ROM | 1 x HP Smart Array P220i controller with 512 MB FBWC, (RAID 0 and 1) or 1 x HP Dynamic Smart Array B320i controller (SATA RAID 0 and 1 standard; SAS RAID 0 and 1 standard on pre-configured models and optional with SAS) | 1 x HP Smart Array P220i controller with 512 MB FBWC, supporting RAID 0 and RAID 1 | 1 x HP Smart Array P220i controller with 512 MB FBWC, supporting RAID 0 and RAID 1 | - Entry model: HP Smart Array P420i/ZM (RAID 0, 1, 1+0) - Base model: HP Smart Array P420i/1 GB with FBWC (RAID 0, 1, 1+0, 5, 5+0, 6, 6+0) - Performance model: HP Smart Array P420i/2 GB with FBWC (RAID 0, 1, 1+0, 5, 5+0, 6, 6+0) | HP Smart Array P830i/2 GB FBWC 12 Gbps SAS controller | - Performance models: HP Smart Array P410i/1G FBWC controller - Base models: HP Smart Array P410i/ 512 MB FBWC or Zero Memory controller | HP Smart Array P410i controller with optional FBWC | Integrated HP Smart Array P410i 6 Gbps Serial-Attached SCSI (SAS) RAID controller | - Integrated SAS version 2.0 (6 Gb) HP Smart Array P410i controller with RAID 0 and 1 - P410i 512 MB and 1 GB FBWC options - Optional Smart Array RAID mezzanine controllers (with BBWC and FBWC) for connection to external storage | Embedded HP Smart Array P220i controller The HP Smart Array P220i supports RAID 0 and 1. It includes 512 MB FBWC on pre-configured models and is optional on factory integrated models. | - Integrated SAS version 2.0 (6 Gb) HP Smart Array - P410i controller with RAID 0, 1 and 1 + 0 - Optional Smart Array RAID mezzanine controllers (with BBWC and FBWC) for connection to external storage | HP Smart Array P410i controller; 1 GB memory module with FBWC. Supports RAID 0,1 | Per blade: (x 2 for BL870c and x 4 for BL890c) - 2 embedded HP Smart Array P410i SAS controllers RAID 1, RAID 0, and HBA mode configuration options - 2 embedded SAS read only 512 MB cache, one per Smart Array controller | Highly expandable via external I/O slots accommodate a choice of controllers |
| Internal storage (max.)<br>*One of the following depending on model | Hot-plug*: 2 x 1.2 TB SFF SAS 2 x 1.0 TB SFF SATA 2 x 800 GB SFF SAS SSD 2 x 800 GB SFF SATA SSD | Hot-plug: 2 x 1.0 TB SFF SAS 2 x 1.0 TB SFF SATA 2 x 800 GB SFF SAS SSD 2 x 800 GB SFF SATA SSD | Hot-plug*: 2 x 1.2 TB SFF SAS 2 x 1.0 TB SFF SATA 2 x 800 GB SFF SAS SSD 2 x 800 GB SFF SATA SSD | Hot-plug: 2 x 1.2 TB SFF SAS 2 x 1.0 TB SFF SATA 2 x 800 GB SFF SAS SSD 2 x 800 GB SFF SATA SSD | Hot-plug: 5 x 1.2 TB SFF SAS 5 x 800 GB SFF SAS SSD 5 x 400 GB SFF SATA SSD | Hot-plug: 10 x 1.2 TB SFF SAS 10 x 800 GB SFF SAS SSD 10 x 800 GB SFF SATA SSD | Hot-plug: 8 x 1.0 TB SFF SAS 8 x 1.0 TB SFF SATA 8 x 800 GB SFF SAS SSD 8 x 400 GB SFF SATA SSD | Hot-plug: 8 x 900 GB SFF SAS 8 x 400 GB SFF SAS SSD | - Up to eight SFF hot-plug disk drives or solid state drives - Up to 7.2 TB of internal storage with 900 GB disks | Hot-plug: 2 x 1.2 TB SAS 2 x 1.0 TB SATA 2 x 800 GB SAS SSD 2 x 800 GB SATA SSD | Hot-plug: 2 x 1.2 TB SAS 2 x 1.0 TB SATA 2 x 800 GB SFF SAS SSD | Hot-plug: 4 x 1.2 TB SAS 4 x 1.0 TB SATA 4 x 800 GB SAS SSD 4 x 800 GB SATA SSD | Hot-plug: 2 x 1.2 TB SAS 2 x 1.0 TB SATA 2 x 800 GB SAS SSD 2 x 800 GB SATA SSD | Per blade: x 2 for BL870c and x 4 for BL890c Up to four SFF SAS hot-plug hard drives | For HP Storage solutions please see: www.hp.com/storage/spock |
| Optical drive support | Enclosure-based DVD drive available with c3000 enclosure | Enclosure-based DVD drive available with c3000 enclosure | Enclosure-based DVD drive available with c3000 enclosure | Enclosure-based DVD drive available with c3000 enclosure | Optional: USB DVD-RW | None | Optional: HP Slim SATA DVD-ROM optical drive ejectable for security and serviceability | Slimline DVD-RW drive standard | Up to one HP Slimline DVD-RW or DVD-ROM optical drive | Enclosure-based DVD drive available with c3000 enclosure | Enclosure-based DVD drive available with c3000 enclosure | Enclosure-based DVD drive available with c3000 enclosure | Enclosure-based DVD drive available with c3000 enclosure | None internal to Integrity blade. External USB DVD drive with 7 ft USB extension cable is supported with c7000 enclosures. | Removable media built-in DVD-ROM, accessible from all partitions |
| Network interface controller<br>*Supports FCoE, Flex-10, TCP/IP offload engine, hardware-based accelerated iSCSI, iSCSI boot, and autosensing 10 Gb/1 Gb Ethernet<br>**Dedicated iLO network card | One of the following depending on model: - Pre-configured models: 1 x HP Flex-10 10 Gb 2-port 530FLB FlexLOM* - Configurable models: 1 x HP FlexFabric 10 Gb, 2-port 534FLB FlexibleLOM or HP FlexFabric 10 Gb 2-port 554FLB FlexibleLOM** | 1 x HP FlexFabric 10 Gb 2-port 554FLB FlexibleLOM* or 1 x HP Flex-10 10 Gb 2-port 530FLB FlexibleLOM or 1 x HP Ethernet 10 Gb 2-port 560FLB FlexibleLOM or 1 x HP Ethernet 1 Gb 2-port 361FLB FlexibleLOM** | 1 x HP FlexFabric 10 Gb 2-port 554FLB FlexibleLOM* or HP FlexFabric 10 Gb 2-port 554FLB FlexibleLOM** | 1 x HP FlexFabric 10 Gb 2-port 554FLB FlexibleLOM* 1x HP Flex-10 10 Gb 2-port 530FLB FlexibleLOM 1x HP Ethernet 10 Gb 2-port 560FLB FlexibleLOM** | Some models come standard with 4 x 1 Gb ports while others come with 2 x 10 Gb ports** | FlexibleLOMs choice of 1 Gb, 10 Gb, or 10 Gb Ethernet or converged networking in their embedded adapter. - HP Ethernet 1 Gb 4-port 331FLR FIO Adapter - HP FlexFabric 10 Gb 2-port 534FLR-SFP+ FIO Adapter - HP Ethernet 10 Gb 2-port 560FLR-SFP+ FIO Adapter** | - HP NC375i Integrated Quad Port Gigabit Server Adapter - Optional Dual Port 10GbE upgrade (replaces (2) 1G ports) - HP Ethernet 1 Gb 4-port 331i-SPI Adapter** | Network RJ-45 4 | (2) 2-port Intel® 82575 embedded 10/100/1000 Base-TX LAN (autosensing; RJ45 connector, Wake On LAN support) | Four embedded NC553i 10 Gb FlexFabric converged network adapter ports with FCoE/Ethernet/iSCSI/ Flex-10/TOE; dedicated iLO interface | Two dual-port FlexibleLOM for choice of 10 Gb FlexFabric, 10 Gb Flex-10, 10 Gb Ethernet dedicated iLO network interface | - Six embedded HP NC553i 10 Gb FlexFabric adapter ports supporting autosensing 10 Gb/1 Gb Ethernet, FCoE, Flex-10, TCP/IP offload engine, hardware-based accelerated iSCSI, and iSCSI boot - One Ethernet-specific slot (mezzanine slot 6) supporting a dual-port mezzanine card for a total of eight "embedded" Ethernet adapter ports; dedicated iLO network interface | Two integrated NC551i 2-port FlexFabric 10 Gb Converged Network Adapters supporting stateless TCP/IP offload, TCP offload engine (TOE), Fibre Channel over Ethernet (FCoE) and iSCSI protocol; dedicated iLO network interface | Per blade (x 2 for BL870c and x 4 for BL890c): 2 integrated NC553i 10 Gb FlexFabric adapter ports supporting 10 Gb/1 Gb autosensing Ethernet, FCoE, Flex-10, and TCP/IP offload engine; up to 12 additional Gigabit Ethernet ports via the NC364m, 4-port mezzanine adapter or six additional 10 Gb Ethernet ports via the NC552m or the NC532m 2-port mezzanine adapters | Built-in networking SD2-8s: 32 10GbE NIC ports max. (4 per blade) SD2-16s: 32 10GbE NIC ports max. (4 per blade) SD2-32s: 64 10GbE NIC ports max. (4 per blade) |
| USB support | **Three total:** One internal USB 2.0 connector One micro SD-HC card slot One TPM 1.2 connector | **Three total:** One internal USB 2.0 connector One micro SD-HC card slot One TPM 1.2 connector | **Three total:** One internal USB 2.0 connector One micro SD-HC card slot One TPM 1.2 connector | **Three total:** One internal USB 2.0 connector One micro SD-HC card slot One TPM 1.2 connector | **Seven total:** Two front, four rear, one internal + one internal Micro SD slot | **Eight total:** Two front, four rear, two internal + one internal Micro SD slot | **Six total:** Two front, two rear, two internal + one internal SD slot | **Six total:** Two front (video) Two rear (video, NIC) Two internal | **Four total:** Four USB 2.0 ports | **Three total:** One internal USB 2.0 connector One SD-HC card slot One TPM 1.2 connector | **Three total:** One internal USB 2.0 connector One micro SD-HC card slot One TPM 1.2 connector | **Three total:** One internal USB 2.0 connector One SD-HC card slot One TPM 1.2 connector | **Three total:** One internal USB 2.0 connector One internal micro SD card slot One TPM 1.2 module support | **Three total per blade:** (x 2 for BL870c and x 4 for BL890c) One internal USB port Two external USB ports via SUV cable | **Two total:** Two USB ports for local user interface |
| Redundant power supply | Enclosure-based redundant power (single-phase or three-phase), DC power option | Enclosure-based redundant power (single-phase or three-phase), DC power option | | | Yes | Four (performance model) or two (base models) HP 1500 W Common Slot Platinum Plus hot-plug Power Supplies | Two (base models) or four (performance models) 1200 W Platinum Power Supplies standard | Rear accessible hot-plug power supplies with option for redundancy | Up to two hot-swap power supplies for N+N redundancy | Enclosure-based redundant power (single-phase and three-phase) DC power option | | | | | Each Superdome 2 enclosure supports 12 power supplies (2N or N_N) and four HP Crossbar Fabric Modules (XFMs) |
| Redundant fans | Redundant cooling using multiple hot-pluggable c-Class Active Cool Fans | Redundant cooling using multiple hot-pluggable c-Class Active Cool Fans | | | Hot-plug redundant fans (standard) | Four hot-plug redundant fans | Hot-plug redundant fans (standard) | Eight hot-plug, redundant fans (standard) | Up to six hot-plug fans (N+1 redundancy) | Redundant cooling using multiple hot-pluggable c-Class active cool fans | | | | | Each Superdome 2 compute enclosure supports 15 fans N + 1 |
| Infrastructure management | HP iLO Management Engine, HP Insight Control, HP OneView (option) | HP iLO Management Engine, HP Insight Control, HP OneView (option) | | | HP iLO Management Engine HP Insight Control HP OneView (option) | HP iLO 4 HP Insight Control HP OneView (option) | HP iLO 3 HP Insight Control HP OneView (option) | HP iLO, HP Systems Insight Manager Insight Control Suites and Insight Dynamics for ProLiant, HP Insight Control, HP OneView (option) | HP iLO 3, HP Systems Insight Display LEDs enable diagnosis with the access panel installed | HP iLO 3 HP Insight Control HP OneView (option) | HP iLO Management Engine HP Insight Control HP OneView (option) | HP iLO 3 standard for BladeSystem HP Insight Foundation HP OneView (option) | HP iLO 3 standard for BladeSystem, HP Insight Foundation HP OneView (option) | HP iLO 3 standard for BladeSystem HP Insight Foundation | HP Integrity iLO 3 management |
| Warranty (P: parts, L: labour, OSS: on-site support, NBD: next-business-day on-site) | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr NBD | 3-yr P, 3-yr L, 3-yr on-site limited global warranty | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr OSS | 3-yr P, 3-yr L, 3-yr on-site limited global warranty | 1-year on-site hardware support |
| Recommended support | **Proactive Care 3-year 24 x 7, 4-hour response** U3C18E | **Proactive Care 3-year 24 x 7, 4-hour response** U3B14E | **Proactive Care 3-year 24 x 7, 4-hour response** U3B14E | **Proactive Care 3-year 24 x 7, 4-hour response** U3B14E | **Proactive Care 3-year 24 x 7, 4-hour response** U6H10E | **Proactive Care 3-year 24 x 7, 4-hour response** U2Z68E | **Proactive Care 3-year 24 x 7, 4-hour response** U2Z68E | **Proactive Care 3-year 24 x 7, 4-hour response** H1K92A3 | **Proactive Care 3-year 24 x 7, 4-hour response** H1K92A3 | **Proactive Care 3-year 24 x 7, 4-hour response** U3B32E | **Proactive Care 3-year 24 x 7, 4-hour response** U3B32E | **Proactive Care 3-year 24 x 7, 4-hour response** U3B32E | **Proactive Care 3-year 24 x 7, 4-hour response** U3B32E | **Proactive Care 3-year 24 x 7, 4-hour response** H1K92A3 | **Proactive Care 3-year 24 x 7, 4-hour response** H1K92A3 |
| | **Installation and Startup Service** UR362E | **Installation and Startup Service – c7000 infrastructure** UE602E | **Installation and Startup Service – c7000 infrastructure** UE602E | **Installation and Startup Service – c7000 infrastructure** UE602E | **Installation and Startup Service** U6H60E | **Installation and Startup Service** U4618E | **Installation and Startup Service** U4618E | **Installation and Startup Service** HA113A1 | **Installation and Startup Service** HA113A1 | **Installation and Startup Service – c7000 infrastructure** UE602E | **Installation and Startup Service – c7000 infrastructure** UE602E | **Installation and Startup Service – c7000 infrastructure** UE602E | **Installation and Startup Service – c7000 infrastructure** UE602E | **Installation and Startup Service – c7000 infrastructure** HA113A1 | **Installation and Startup Service** HA113A1 |

## HP Flexible Network Adapters for ProLiant Gen8 Servers

| | ProLiant BL | | | | | | | | | | | | | | ProLiant DL/SL/ML | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Adapter** | HP 530 | HP NC532 | HP NC542 | NC552 | HP 544 (FDR/QDR) | HP 630 (Baird and BrWood) | | | HP 534 | HP NC551 | HP NC553 | HP 554 | HP 560 | 361FLB | 366M | 544QSFP | HP InfiniBand 4 x QDR ConnectX-2 PCI-e G2 dual-port HCA | | HP NC523 | HP 526 | 530FLR/SFP/T | 531 | HP 533 | HP 534FLR | HP NC550SFP 10 Gb 2-port PCI-e x 8 Ethernet Adapter | 554 | 560 | 561 | 570 | HP 571 | 331FLR/T | HP 332T | 360 | 361T | HP NC364 | HP NC365 | 366FLR | HP NC112T PCI-e | |
| **Number of ports** | 2 | 2 | 2 | 2 | 2 | 2 | | | 2 | 2 | 2 | 2 | 2 | 2 | 4 | 2 | 2 | | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | | 2 | 2 | 2 | 2 | 2 | 4 | 2 | 2 | 2 | 4 | 4 | 4 | 1 | |
| **Transfer rate** | 10000 (10GbE) | | | | (10/40 Gb/s) | 20000 (20GbE) | | | 10000 (10GbE) | | | | 10000 (10GbE) | 10/100/1000 | 10000 | 10/40 Gb/s | 10000 | | 10000 | 10000 | 10000 | | | | | 10000 | | | | | | 10/100/1000TX | 1000 | | | | | 1000 | 1000 | |
| **VC Flex10, FlexFabric, CNA** | VC Flex-10 | | | | CNA (IB/Ethernet) | Flex10, FlexFabric, CNA (iSCSI/FCOE) | | | Flex10, FlexFabric, CNA (iSCSI/FCOE) | | | | NIC | | IB | IB | IB | | NIC | | NIC | | | | | NIC | | | | | | NIC | | | | | | NIC | NIC | |
| **PCI bus architecture** | PCI-e v 2.0 | | | | PCI-e Gen3 | PCI-e v 2.0 | | | PCI-e v 2.0 | | | | PCI-e v 2.0 | | | PCI-e Gen3 | PCI-e v 2.0 | | PCI-e v 2.0 | | PCI-e v 2.0 | | | | | PCI-e v 2.0 | | | | | | PC